

AQUA UNDERWATER SPOTLIGHT | ULTRA OUTPUT

The AXS 36 is a high-power multi-LED underwater drum light designed for larger-scale pools, fountains, and feature water installations. With 36 high-power LEDs delivering up to 36W in RGBW, RGBA, RGB, Dynamic White or mono-colour configurations, it provides exceptional output and vibrant colour mixing.

Beam angles range from 10° to 60° with optional encapsulated lenses for precise distribution.

Built from die-cast 316L marine-grade stainless steel and rated IP68 to 6m depth, the AXS 36 pairs with an external constant current driver supporting daisy-chains of up to four units.



At a glance

Emitters

RGBW
(W = 2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6000K)

OR

RGBA

OR

RGB

OR

Dynamic White (DW)
(2000K to 5000K)

OR

White
(2700K, 3000K, 3500K, 4000K)

Certifications

Dimensions

Controls

Voltage

24v DC

Protection

Ingress – IP68

Temperature

-20°C to 50°C
-4°F to 122°F

Optics

FIXTURE PRODUCT CONFIGURATOR

Prefix	Model	LED Colour	White CCT	Control	Beam Angle	Power	Voltage
AXS	36	RGBW RGBA RGB DW – Dynamic White (20K - 50K) W – White	24K – 2400K 27K – 2700K 30K – 3000K 35K – 3500K 40K – 4000K 50K – 5000K 60K – 6000K	D – DMX	10 – 10° 25 – 25° 40 – 40° 1.3 – 10°x35° 1.6 – 10°x60°	36 – 36W	24 – 24v DC

EXAMPLE: AXS – 36 – RGBW – 40K – D – 25 – 36 – 24

AQUA UNDERWATER SPOTLIGHT | ULTRA OUTPUT


FIXTURE SPECIFICATIONS

ELECTRICAL	POWER CONSUMPTION OPERATING VOLTAGE OPERATING TEMPERATURE STORAGE TEMPERATURE	36W MAX 24V DC -20°C TO 50°C (-4°F TO 122°F) -20°C TO 70°C (-4°F TO 158°F)
PHYSICAL	FIXTURE DIMENSIONS IP RATING SOURCE LIFE HOUSING CONNECTION ACCESSORIES	Ø: 193MM – H: 144MM IP68 WITH 6M DEPTH 50,000 TO 70,000 HOURS/L70 AT 25°C DIE-CAST, 316L STAINLESS STEEL HOUSING FOR MARINE APPLICATION 20M INPUT CABLE WITH BARE TAIL, ENCAPSULATED IN-GRADE KIT (NEED TO BE ORDERED SEPARATELY)
OPTICAL	BEAM ANGLE COLOUR RANGE ACCURATE COLOUR CONTROL LED TYPE LIGHT SOURCE	10° – (25° – 40° – 10°X35° – 10°X60° OPTIONAL) WITH ENCAPSULATED WHITE (2400K, 2700K, 3000K, 3500K, 4000K, 5000K, 6000K), RGB, DYNAMIC WHITE (2000K – 5000K) RGBW CONFIGURATIONS WITH SELECTABLE CCT HIGH POWER LEDS 36PCS LEDS
DIMING & CONTROL	CONTROL PROTOCOLS	DMX/RDM PROTOCOL, ADDRESSED BY RDM
FIXTURE RATING & CERTIFICATIONS	CE / IP68	 
LIMITED WARRANTY	5 YEARS *Extendable warranty available	


AQUA UNDERWATER SPOTLIGHT | ULTRA OUTPUT

FIXTURE DIMENSIONS

AXS 36 FIXTURE DIMENSIONS



AXS 36 FIXTURE DIMENSIONS – IN-GROUND VERSION



FIXTURE DIMENSIONS

AXS 36 FIXTURE DIMENSIONS – TECHNICAL DRAWING INSTALLATION

*Note: Please refer to the below instructions for inground installation

